


LEUPOLD®

Leupold® DeltaPoint® Pro Reflex Sight

Mounting & Operation Instructions

Operating Instructions

For optimum performance and to prevent damage to this precision instrument, carefully follow all instructions.



Features

- DiamondCoat™, scratch resistant aspheric lens for brightness, and resolution
- Motion Sensor Technology (MST™)
- Night vision w/user adjustable settings (on select models)
- Extremely durable, ultra light aluminum housing
- Small size and lightweight
- Unlimited eye relief
- For handguns, rifles and shotguns
- Wide field of view
- Blackened lens edges
- Waterproof to 33ft.


Specifications

- Magnification: 1.0x
- Sight window: 25.7mm x 17.5mm; 1.01" x 0.68"
- Elevation adjustment range: 60 MOA
- Windage adjustment range: 60 MOA
- 40 MOA per revolution of adjustment (1 MOA per click)
- Subtension of the aiming point: 2.5 MOA Dot or 6.0 MOA Dot
- Operating Temperature Range: -20°F to +120°F (-29°C to +49°C)
- Storage Temperature Range: -40˚F to +160˚F (-40˚C to +71˚C)
- Power Supply: 3V with one CR 2032 Lithium battery
- Dimensions: (LxWxH) 1.82" x 1.31" x 1.30" (46.1mm x 33.2mm x 33.0mm)
- Weight (with battery installed): 1.9oz. (53.8g)


Package Contents

- DeltaPoint Pro Reflex Sight, 2.5 MOA Dot (SKU 119688, 175840, 177156, 179585 or 179586)
- DeltaPoint Pro Reflex Sight 6.0 MOA Dot (SKU 181105 or 181106)
- (1) 3V Lithium battery (CR 2032)
- (1) Protective cover
- (2) M4x.7x15.8mm Torx® head screws for installing the sight on the mounting plate
- (1) Torx® T-15 wrench
- (1) 1/16 Hex wrench
- Operating Instructions

⚠ WARNING



- **INGESTION HAZARD: DEATH** or serious injury can occur if ingested.
- A swallowed button cell or coin battery can cause **Internal Chemical Burns** in as little as **2 hours.**
- KEEP new and used batteries **OUT OF REACH OF CHILDREN.**
- **Seek immediate medical attention** if a battery is suspected to be swallowed or inserted inside any part of the body.





Battery Installation

The unit operates with one commercially available 3V Lithium battery (CR 2032) only. Open the battery cover by pulling back the battery door release latch. Insert the battery so the positive side (+) is facing up and close the battery cover. Push the battery door release latch into place. Verify the white witness mark is fully covered by the latch. Keep the contact surface clean of dirt and corrosion, cleaning with alcohol if necessary.

Illumination Operation

DeltaPoint Pro is equipped with eight illumination intensities. To activate the DeltaPoint Pro press and release the power button. Cycling through the illumination intensities is done by repeatedly pressing and releasing the power button. When the highest or lowest setting is reached, the LED will flash 5 times. To change the direction of adjustment, i.e., change from increasing intensity to decreasing intensity, press and hold the power button for 2 seconds and immediately release the button. Then continue pressing and releasing to change intensity.

To power the DeltaPoint Pro off, press and hold the power button for approximately 3 seconds, or until the LED turns off. When reactivated, the unit will return to the last known setting.

DeltaPoint Pro NV (Night Vision)

The DeltaPoint Pro NV is designed to work with the latest generation of white phosphor night vision devices. It offers 10 brightness settings, increasing from night vision (levels 1 and 2) to daytime bright (level 10).

To activate the DeltaPoint Pro NV, press and release the power button. Cycle through the brightness settings by repeatedly pressing and releasing the power button. When the highest or lowest setting is reached, the sight will flash 5 times. The night vision settings (levels 1 and 2) have been pre-set to accommodate most current night vision devices, but these settings can be adjusted to meet the requirements of your specific night vision device.

Brightness Adjustment Operation

Shooters using night vision optics in combination with the DeltaPoint Pro NV may desire to fine tune the intensity of levels 1 and 2 to optimize performance. Shooters may also adjust the brightest setting, level 10, to best match daylight shooting conditions.

The brightness of levels 1, 2, and 10 can be increased in increments of 25% (to a maximum of 250%), or decreased in increments of 5% (to a maximum of 40%). All luminosity adjustments are preserved even if the battery is removed.

If you find it difficult to toggle the button and see the aiming dot at the same time, then use a narrow tool with a flat base (like the eraser end of a pencil) to adjust the brightness settings with ease. Do not use a sharp tool or anything that could potentially damage the button.

To increase brightness:

- Ensure the sight is set at level 1, 2 or 10.
- Turn the sight OFF by holding the button down for approximately 3 seconds and then releasing.
- Now, press and hold the button down for approximately 8 seconds. The sight will turn on, then turn off, and then flash at the new brightness intensity to acknowledge the change request.
- Once the acknowledgement flash has occurred, release the button.

Repeat steps 2 through 4 to continue increasing the brightness. Once maximum brightness has been reached, the acknowledgement flash will be 2 seconds in duration.

Note: Battery life will be reduced if the level 10 intensity is adjusted brighter than factory default settings.

To decrease brightness:

- Ensure the sight is turned on and set at level 1, 2 or 10. (Do not turn the sight off.)
- Press and hold the button down for approximately 8 seconds. The sight will turn off, and then flash at the new brightness intensity to acknowledge the change request.
- Once the acknowledgement flash has occurred, release the button.

Repeat steps 2 and 3 to continue decreasing the brightness. Once minimum brightness has been reached, the acknowledgement flash will be 2 seconds in duration.

***NOTE:** Decreasing brightness occurs in smaller increments than when increasing it, allowing users to fine tune the brightness of levels 1, 2, and 10.*

Factory reset:

If you want to start over, you can easily reset the DeltaPoint Pro NV to factory default settings.

- Turn the sight on.
- Hold the button down for approximately 30 seconds.

After 30 seconds, the sight will flash at high brightness, indicating that it has returned to factory reset settings.

- Release the button.

The sight will continue to flash at high brightness for 3 seconds after the button is released. All brightness adjustments are removed. The sight will then turn off (i.e. stop flashing).

The next time the sight is turned on, it will be set at level 8 of 10, and levels 1, 2, and 10 will be returned to factory default settings.

Low Battery Indicator

The DeltaPoint Pro has a unique feature that flashes the aiming point 10 times when low battery power is detected. The operator will have several hours of operating time in this mode before the sight is rendered inoperable without a battery change.

Power-Saving Mode (Motion Sensor Technology™)

After the optic has been completely at rest for 5 minutes the sight transfers to sleep mode, thus nearly eliminating all battery drain. Upon any movement of the optic, the system powers up the LED to the last known setting. The unit will flash 10 times before automatic power off. The motion sensor will NOT reactivate the DeltaPoint Pro if it has been turned off manually.

CAUTIONS & WARNINGS:

Check to ensure that the magazine of the firearm has been removed or emptied, that the action is open, and that there is not a round in the chamber. Only after double checking the firearm, verifying it is empty and safe, should you proceed with the installation of the DeltaPoint Pro.

Installation

***NOTE:** If you are installing the DeltaPoint Pro on a milled slide, or Glock MOS the mount base & dovetail are not required. Installation on most handguns requires the use of one of the optional mount bases (sold separately). Leupold recommends utilizing a qualified gunsmith to press/remove the rear sight from your handgun. Once the rear sight has been removed, the appropriate dovetail replaces the rear sight, with the part number facing up. Some installations (Kimber / Smith & Wesson M&P) require the use of the set screws to be placed in the dovetail to hold it in place and the M4x.7x15.8mm Torx screws will fasten into the dovetail plate extension.*


(Figure 1) M4x.7x15.8mm Torx Screws; Mount Base; Dovetail; Pistol Slide

The corresponding mount base for your pistol is placed on top of the slide and over the dovetail with the flat part number side facing up through the slot in the base. Once the dovetail and mount base have been placed on the slide, the DeltaPoint Pro is placed on top of the base. The four holes in the bottom of the DeltaPoint Pro will align with the four short posts on the mount base and secure into the dovetail using the two included M4x.7x15.8mm Torx screws **(Figure 1)**. Secure the screws by applying 25 in-lbs of torque. Securing these screws creates a press-fit and will hold the DeltaPoint Pro firmly in place. For Smith & Wesson M&P Core / FNX handguns, check the adapter plate torque every 1000 rounds. Call Leupold customer service for details specific to your handgun. For rifle/shotgun applications, the Cross-Slot Mount allows fast and easy mounting on Weaver-style or Picatinny bases/rails.

Smith & Wesson® Revolver Mount

(For use with Smith & Wesson Classic pre-drilled and tapped K, L, N & X frame revolvers, including .500)

Remove the rear sight and retain the sight and all mounting hardware for future use if necessary. Place the insert (10A) into the mount base (10B) and set both pieces on the revolver as shown below. Install the two 6-48x .210 screws through the dovetail insert and into the last two tapped holes, nearest the hammer in the frame of the revolver **(Figure 2)**. Tighten to 22 in-lbs.



Place the DeltaPoint Pro on the mount base so that the four holes in the bottom of the DeltaPoint Pro will align with the four short posts on the mount base. Then secure the sight with the two M4x.7x15.8mm screws using 25 in-lbs of torque.

Operating Procedure

Elevation and Windage Adjustment

Separate controls for the elevation and windage adjustments are found on the top and right side of the sight. Turn the UP or "R" (RIGHT) screws with a screwdriver, cartridge rim or coin. The windage adjustment mechanism has limit stops at both ends.

Zeroing the Point-of-Impact

The DeltaPoint Pro windage and elevation screws move the point of impact 40 MOA (10" @ 25 yds) per revolution of the dial (1 MOA per click).

Boresighting the DeltaPoint Pro Reflex Sight

To make the boresighting process easier, Leupold recommends placing the eye near the DeltaPoint Pro while making windage/elevation adjustments. As with any boresighting procedure, be sure to follow all safety precautions prior to boresighting, and make sure the boresighter has been removed from the barrel prior to loading the magazine or chamber.

CAUTION: BORESIGHTING THE DELTAPOINT PRO

Verify that the magazine of the firearm has been removed or emptied, and that there is not a round in the chamber. Only after double checking the firearm, verifying it is empty and safe, should you proceed with the boresighting process. Be sure to remove the boresighter from the the barrel prior to loading the magazine or chamber.

Leupold Product Service

If your Leupold Gold Ring scope fails to perform in any way, you may return it directly to the factory (or one of our international service centers) for service. To return a product for service from within the U.S. follow these shipping instructions:

1. Remove the rings and any other accessories from the scope.
2. Record the serial number of the scope and keep it for your records.
3. Visit leupold.com/rma/warranty/create and follow the instructions there to start the warranty process. When shipping the product, include the Packing Slip that will be provided.
4. Pack the scope in its original box (if you have it), as this is the safest shipping container. Wrap the package securely using filament strapping tape on the outside.
5. Ship the scope by a traceable parcel or mail service (insured, if possible) to one of the following addresses:

Register your product at: leupold.com/product_registration/product

IN THE UNITED STATES:

Parcel or Mail Service:
Leupold Product Service
14400 NW Greenbrier Parkway
Beaverton, OR 97006-5790 USA

Our Product Service telephone numbers are:

Local (503) 526-1400

Toll-Free 1(800) LEUPOLD (538-7653)

Fax (503) 352-7621

OUTSIDE THE UNITED STATES:

Canada: Korth Group Ltd., 64186- 393 Loop East, Okotoks, AB T1S 0L1, Canada

Australia: Nioa, 80 Lomandra Drive, Eagle Farm, Qld 4009, Australia (for items originating from Australia, New Zealand, New Caledonia and Japan)

South Africa: Formalito, 1019 Pretorius Ave. Lyttelton Manor, 0157, South Africa

Leupold & Stevens, Inc. products, parts, components, technical data, and services may be controlled for export and import, by the U.S. Department of State under the International Traffic in Arms Regulations (22 CFR, Parts 120-130) or the Department of Commerce under the Bureau of Industry and Security Export Administration Regulations, EAR (15 CFR, Parts 730-774). Diversion contrary to U.S. law prohibited. Email: compliance@leupold.com for export classification and guidance on specific items.


Accessories (sold separately)

Single Base/Dovetail available for the following firearms:

- **Glock®** (SKU 170906)
- **Smith & Wesson M&P C.O.R.E** (SKU 171203)
- **Marlin 336** (SKU 172645)
- **Smith & Wesson M&P** (SKU 170909)
- **1911 Standard** (SKU 170904)
- **SIG SAUER P226** (SKU 170908)
- **Smith & Wesson Classic** (SKU 170911)
- **Beretta 92** (SKU 170902)



AR DLOC (171861)
- Allows the DeltaPoint Pro to be installed at perfect height for AR platforms
- Quick detachment with square recoil lugs




AR MOUNT (177154)
- Puts the DP Pro to the right height for AR's
- Fits any Picatinny rail
- Precision machined from aerospace-grade aluminum



45° MOUNT (173236)
- Easily attaches directly to Picatinny rails
- Mounts on left or right side
- Fits DeltaPoint Pro red dot only

REVERSIBLE CROSS-SLOT MOUNT (120056)
- For installing the DeltaPoint Pro on Picatinny rails and Weaver-style bases





CROSS-SLOT RISER (120059)
- Used in conjunction with the DeltaPoint Pro Reversible Cross-Slot Mount to achieve proper height and match alignment of cheek-to-stock weld when installing the DeltaPoint Pro on an AR style rifle





REAR IRON SIGHT (120058)
- Allows for co-witnessing through the DeltaPoint Pro on a handgun
- Faster reticle acquisition and a sure-fire backup in case of battery failure. A taller front sight is required when using the Rear Iron Sight



RING TOP MOUNT KIT (175541, 175550, 175554, 175558)
- Available in 1", 30mm, 34mm and 35mm
- Provides secure installation for DeltaPoint Pro on top of Mark 4 rings and IMS mounts. (not compatible with Mark 2 IMS mounts)
- Base plate and hardware included.

Leupold Lifetime Guarantee

Anyone can offer you a lifetime warranty, but guaranteeing performance takes serious dedication and craftsmanship. From our Beaverton Oregon factory, to the wilderness, the battlefield, and everywhere in-between, we won't let you down.


If your Leupold scope, red dot sight, binocular or spotting scope doesn't perform, we will repair or replace it for free, whether you're the original owner or not – forever.

For complete details visit leupold.com/support/lifetime-guarantee

Leupold & Stevens, Inc.

PO Box 688, Beaverton, OR 97075-0688
leupold.com 1-800-LEUPOLD (538-7653)

Part #120278 Artwork #120279P



Remove and immediately recycle or dispose of used batteries according to local regulations and keep away from children. Do NOT dispose of batteries in household trash or incinerate. Even used batteries may cause severe injury or death. Call a local poison control center for treatment information. Non-rechargeable batteries are not to be recharged. Do not force discharge, recharge, disassemble, heat above (manufacturer's specified temperature rating) or incinerate. Doing so may result in injury due to venting, leakage or explosion resulting in chemical burns. Ensure the battery is installed correctly according to polarity (+ and -). Do not mix old and new batteries, different brands or types of batteries, such as alkaline, carbon-zinc, or rechargeable batteries. Remove and immediately recycle or dispose of batteries from equipment not used for an extended period of time according to local regulations. Always completely secure the battery compartment. If the battery compartment does not close securely, stop using the product, remove the batteries, and keep them away from children.




Viseur Reflex Leupold®Delta Point® Pro

Instructions de montage et d'utilisation

INSTRUCTIONS D'UTILISATION

Pour obtenir des performances optimales et prévenir tout dommage à cet instrument de précision, nous vous recommandons de suivre avec attention la totalité des instructions de montage et d'utilisation.



CARACTÉRISTIQUES

- Lentilles asphériques traitées DiamondCoat™ pour une grande résistance à l'abrasion et une clarté et luminosité optimales
- Technologie Motion Sensor (MST™)
- Boitier en aluminium léger pour une grande durabilité
- Petite taille et poids léger
- Dégagement oculaire sans limite
- Utilisable sur armes de poing, fusils lisses et carabines rayées
- Large champ de vision
- Entourage des lentilles anti reflets teinté noir
- Étanche jusqu'à 10 mètres

SPÉCIFICATIONS

- Grossissement x 1.0
- Dimensions de l'écran de visée : 25,7 mm x 17,5 mm
- Plage de réglage en hauteur : 60 MOA
- Plage de réglage en dérive : 60 MOA
- 40 MOA de réglage par tour complet (1 MOA par click)
- Sous-tension du point de visée : 2,5 MOA pour Dot, et 6,0 MOA pour Dot
- Plage de températures d'utilisation : de -29°C à + 49°C
- Plage de températures de stockage : de -40°C à + 71°C
- Énergie fournie par une pile lithium 3V CR 2032
- Dimensions (longueur – largeur- hauteur) : 46,1mm x 33,2 mm x 33,0 mm
- Poids (avec pile): 53,8 grammes

CONTENU DE LA BOITE


- Viseur Delta Point Reflex 2,5 MOA (SKU 119688, 175840, 177156 or179585 or 179586)
- Viseur Delta Point Reflex 6,0 MOA (SKU 181105 or 181106)
- 1 pile lithium 3 Volts (CR 2032)
- 1 capot de protection
- 2 vis Torx® M4 7x15,8 mm pour l'installation du viseur sur la plaque de montage
- 1 clé Torx® T-15
- 1 clé 6 pans 1/16
- Instructions d'utilisation

⚠ AVERTISSEMENT

- **RISQUE EN CAS D'INGESTION : LA MORT** ou des blessures graves peuvent survenir en cas d'ingestion.
- Une pile bouton ou batterie avalée peut causer des **brulures chimiques internes** en moins de **2 heures**.
- Conserver les piles neuves et usagées **HORS DE PORTEE DES ENFANTS**.
- **Consulter immédiatement un médecin** en cas de suspicion de pile avalée ou insérée dans une partie du corps.







INSTALLATION DE LA PILE

Ce viseur fonctionne grâce à une pile 3V au lithium (CR 2032) disponible dans le commerce. Ouvrez le couvercle du logement de pile en tirant le loquet de verrouillage du couvercle vers l'arrière. Insérez la pile avec le côté positif (+) en haut, puis refermez le couvercle du logement. Repoussez le loquet de verrouillage du couvercle en place. Assurez-vous que le repère blanc est bien caché sous le loquet. Gardez la surface du contact propre et sans poussière. Si nécessaire, nettoyez-le à l'alcool dénaturé.

FONCTIONNEMENT DE L'ILLUMINATION

Le DeltaPoint Pro possède huit intensités d'illumination. Pour activer le Deltapoint Pro, pressez puis relâchez le bouton Marche/Arrêt. Pour modifier l'intensité d'illumination, vous devez presser puis relâcher le bouton de mise en route jusqu'à arriver à l'intensité désirée. Lorsque le point le plus haut ou le plus bas d'illumination est atteint, le LED clignote cinq fois. Pour changer le sens de progression de l'intensité d'illumination, comme par exemple passer de l'accroissement à un affaiblissement de l'intensité, pressez sans le relâcher le bouton de mise en route pendant deux secondes, puis relâchez immédiatement ce bouton. Pour éteindre le DeltaPoint Pro, pressez sans le relâcher le bouton de mise en route pendant environ trois secondes, ou bien jusqu'à ce que le LED s'éteigne. Lorsque vous rallumez le DeltaPoint Pro, l'intensité d'illumination sera la dernière utilisée.

DELTAPOINT PRO NV (NIGHT VISION)

Le DeltaPoint Pro NV possède dix réglages d'illumination, augmentant la luminosité du point rouge en faible condition de lumière (niveaux 1 et 2) et restant visible avec une très forte luminosité de jour (niveau 10). Pour activer le DeltaPoint Pro NV, appuyez et relâchez le bouton d'alimentation. Faites défiler les réglages d'intensité en appuyant et en relâchant le bouton d'alimentation de manière répétée. Lorsque l'intensité la plus élevée ou la plus faible est atteinte, le point LED clignote 5 fois.

REGLAGE DE LA LUMINOSITE

Les tireurs qui utilisent des optiques de vision nocturne en combinaison avec le DeltaPoint Pro NV peuvent souhaiter régler l'intensité aux niveaux les plus bas afin d'obtenir la meilleure performance possible. Certains utilisateurs peuvent également souhaiter régler l'intensité au niveau le plus élevé pour s'adapter au mieux à leurs conditions de tir.

Pour ce faire, l'intensité des niveaux 1, 2 et 10 peut être augmentée ou diminuée. Les niveaux 1 et 2 sont destinés à la vision nocturne uniquement. Le niveau 10 est le réglage de luminosité le plus intense disponible sur le DeltaPoint Pro NV.

La luminosité de ces trois niveaux peut être ajustée entre 40% et 250% des paramètres par défaut. La luminosité peut être augmentée par tranche de 25% ou diminuée par tranche de 5%. Tous les réglages de luminosité sont conservés même si la batterie est retirée.

Si vous trouvez qu'il est difficile d'appuer sur le bouton, utilisez alors un outil étroit à base plate (comme l'extrémité à gomme d'un crayon à papier) pour régler la luminosité.

POUR AUGMENTER LA LUMINOSITÉ :

1. S'assurer que le viseur est réglé au niveau 1, 2 ou 10.
2. Eteindre la visée en maintenant le bouton enfoncé pendant environ 3 secondes le relacher.
3. Appuyez sur le bouton et maintenez-le enfoncé pendant environ 8 secondes.

Le point s'allume, s'éteint, puis clignote à la nouvelle intensité de luminosité pour valider la demande de changement.

4. Une fois que le flash de validation s'est produit, relâcher le bouton.

Répétez les étapes 2 à 4 pour continuer à augmenter la luminosité. Une fois la luminosité maximale atteinte, le flash de validation aura une durée de 2 secondes.

Remarque : La durée de vie de la pile peut être réduite si la luminosité est supérieure aux réglages d'usine.

POUR DIMINUER LA LUMINOSITÉ :

1. S'assurer que le viseur est réglé au niveau 1, 2 ou 10.
2. Appuyez sur le bouton et maintenez-le enfoncé pendant environ 8 secondes.

Le point s'éteint, puis clignote à la nouvelle intensité de luminosité pour valider la demande de changement.

3. Une fois que le flash de validation s'est produit, relâcher le bouton.

Répétez les étapes 2 et 3 pour continuer à baisser la luminosité. Une fois la luminosité minimale atteinte, le flash de validation aura une durée de 2 secondes.

***REMARQUE :** La diminution de la luminosité se réalise par des palliers plus faibles que l'augmentation de la luminosité, ce qui permet aux utilisateurs de régler précisément la luminosité de leur DeltaPoint Pro NV.*

POUR REVENIR AUX RÉGLAGES D'USINE :

Vous pouvez facilement remettre le DeltaPoint Pro NV aux paramètres d'usine.

1. Allumer le point rouge.
2. Maintenez le bouton enfoncé pendant environ 30 secondes.

Au bout de 30 secondes, le point clignote à haute intensité, indiquant que les réglages sont revenus à leurs srtis d'usine.

3. Relâchez le bouton.

Le point continuera à clignoter à haute intensité pendant 3 secondes après avoir relâcher le bouton. Tous les réglages de luminosité sont supprimés. Le point s'éteint (cesse de clignoter).

Lors du prochain allumage du point , le réglage d'intensité sera de 8 sur 10.

INDICATEUR DE PILE FAIBLE

Le DeltaPoint Pro est équipé d'un dispositif particulier qui fait clignoter dix fois le point central de visée dès qu'une faiblesse de charge de la pile est détectée. L'opérateur a alors plusieurs heures d'utilisation devant lui avant l'arrêt total de l'appareil si la pile n'est pas remplacée.

MODE ÉCONOMIE D'ÉNERGIE (MOTION SENSOR TECHNOLOGY™)

Après cinq minutes au repos et sans mouvement, le viseur passe en mode veille, ce qui élimine pratiquement toute déperdition d'énergie de la pile. Au moindre mouvement de l'optique, le système rallume la LED sur le dernier réglage utilisé. L'illumination clignote dix fois avant l'arrêt automatique. Le Motion Sensor ne réactive pas le DeltaPoint Pro si il a été coupé manuellement.



CAUTIONS & WARNINGS:

Assurez-vous que le chargeur de votre arme à feu est vide ou a été enlevé, que la culasse est ouverte et qu'il n'y a pas de cartouche dans la chambre. Ce n'est qu'après avoir contrôlé par deux fois que votre arme est vide et en sécurité que vous pourrez commencer à installer le DeltaPoint Pro.

INSTALLATION

***REMARQUE :** si vous installez le DeltaPoint Pro sur une culasse déjà usinée ou sur un Glock MOS, l'embase et le montage pour queue d'aronde ne sont pas nécessaires. Le montage sur une arme de poing nécessite l'emploi d'une des embases optionnelles (vendues séparément). Leupold recommande de recourir aux services d'un armurier qualifié pour retirer la hausse de votre arme de poing. Une fois cette hausse retirée, la queue d'aronde dédiée à votre arme peut être installée en lieu et place de la hausse d'origine. Certains montages (sur Kimber ou Smith & Wesson) nécessitent l'emploi de vis de blocage pour un maintien ferme en place ; les vis Torx® M4x 7x15,8 mm seront vissées dans la queue d'aronde pour bloquer la plaque d'extension.*

Le montage correspondant à votre arme de poing est disposé au-dessus de la culasse et de la queue d'aronde avec la face plate portant le numéro sur le haut et visible à travers la fente usinée dans l'embase. Lorsque la queue d'aronde et l'embase sont positionnées sur la culasse, le DeltaPoint est placé au dessus de l'embase. Les quatre trous de la base du DeltaPoint sont alignés avec les quatre plots de vissage de l'embase de montage et seront reliés par les deux vis torx® M4x 7x15,8 mm (illustration 1). Serrez les vis à un couple de 25 inch/pound. La fixation ferme obtenue à l'aide de ces vis va créer un ajustage par pression entre les pièces qui empêchera tout mouvement du DeltaPoint. Pour les armes de poing type Smith & Wesson M&P Core / FNX, vous devez contrôler le couple de serrage tous les mille coups. Vous pouvez joindre le Service technique Leupold pour toute information spécifique relative à votre arme de poing. Pour une installation sur fusil lisse et carabine, le montage Cross-Slot vous permet un montage rapide et facile sur une embase ou rail type Weaver ou Picatinny.

Illustration 1

Vis Torx M4.7x15,8 mm

Embase de montage

Queue d'aronde

Culasse du pistolet

MONTAGE SUR REVOLVER SMITH & WESSON®

(Pour montage sur revolvers Smith & Wesson Classic pré-percés et filetés (carcasses K,L;N et X, caliber .500 inclus).

Démontez la hausse et rangez-la soigneusement pour une éventuelle utilisation ultérieure. Placez l'insert 10A dans l'embase de montage (10B), puis positionnez ces pièces sur le revolver comme montré ci-dessous. Vissez les deux vis 6x48 .210 à travers l'insert dans les deux filetages à l'arrière de la carcasse illustration 2). Serrez les vis au couple de 22 in-lbs.

2 vis 6x48 .210

(Illustration 2

Insert 10A

Embase de montage 10B

Positionnez leDeltaPoint au dessus de l'embase de sorte que les quatre trous de la base du DeltaPoint soient alignés avec les quatre plots de vissage de l'embase de montage (illustration 3). Serrez les vis les deux vis M4x 7x15,8 mm à un couple de 25 inch/pound pour une fixation ferme et sûre.

PROCÉDURE DE FONCTIONNEMENT

RÉGLAGES EN HAUTEUR ET EN DÉRIVE

Les commandes séparées de réglages en hauteur et en dérive se situent sur le dessus et à droite du viseur. Faites tournez les vis marquées UP ou « R » (droite) à l'aide d'un tournevis, du bourrelet d'une cartouche ou d'une pièce de monnaie. Le mécanisme de réglage en dérive est doté d'arrêts en fin de course à ses deux extrémités.

ZÉROTAGE DU POINT D'IMPACT

Les vis de réglage en hauteur et dérive du DeltaPoint font bouger le point d'impact de 40MOA (10 à 25 mètres) par tour complet de la tête de vis (1 MOA par click).

SIMBLEAUTAGE DU VISEUR DELTAPOINT REFLEX AVEC UN COLLIMATEUR

Pour réaliser un simbleautage facile, leupold recommande de placer l'œil près du DeltaPoint Pro pendant les ajustements en hauteur et en dérive. Comme lors de toute opération de simbleautage, vous devez respecter les consignes de sécurité avant d'installer le collimateur. Vous vous assurerez d'avoir retiré le collimateur du canon avant de remplir le chargeur ou d'introduire une cartouche dans la chambre.

AVERTISSEMENT :

Assurez-vous que le chargeur de votre arme à feu est vide ou a été enlevé, que la culasse est ouverte et qu'il n'y a pas de cartouche dans la chambre. Ce n'est qu'après avoir contrôlé par deux fois que votre arme est vide et en sécurité que vous pourrez commencer le simbleautage à l'aide d'un collimateur. Assurez-vous de bien avoir retiré le collimateur du canon avant de remplir le chargeur ou d'introduire une cartouche dans la chambre.

SERVICE TECHNIQUE PRODUITS LEUPOLD

Si votre lunette Leupold ne fonctionne pas bien, vous pouvez contacter un Spécialiste du Service qui déterminera si le problème peut être résolu sans le retour du produit à l'usine. La plupart de ces problèmes sont souvent résolus à distance. Le Service Technique Leupold vous apportera toute son aide.

POUR CONTACTER LE SERVICE TECHNIQUE LEUPOLD

TÉLÉPHONE :
7h30 à 14h30. Lundi au Vendredi:
1-800 LEUPOLD ou (503) 575-1400

FAX :
(503) 352-7621

E-MAIL :
productspecialist@leupold.com

TRANSPORTEUR :
Leupold Product Service
14400 NW Greenbrier Parkway
Beaverton, OR 97006-5791 USA

SERVICE POSTAL :
Leupold Product Service
P.O. Box 688
Beaverton, OR 97075-0688 USA

ACCESSOIRES (VENDUS SÉPARÉMENT)

MONTAGES DISPONIBLES :

- **Glock®** (SKU 170906)
- **Smith & Wesson M&P C.O.R.E** (SKU 171203)
- **Marlin 336** (SKU 172645)
- **Smith & Wesson M&P** (SKU 170909)
- **1911 Standard** (SKU 170904)
- **SIG SAUER P226** (SKU 170908)
- **Smith & Wesson Classic** (SKU 170911)
- **Beretta 92** (SKU 170902)



AR DLOC (171861)



HAUSSE MÉTALLIQUE DELTAPOINT PROAUXILIAIRE (120058)

MONTAGE POUR AR (177154)



MONTAGE CROSS SLOT RÉVERSIBLE POUR DELTAPOINT PRO (120056)

PLAQUE CROSS-SLOT DE SURÉLÉVATION DU DELTAPOINT PRO (120059)

KIT DE MONTAGE SUPÉRIEUR DE BAGUE (175550, 175554, 175558)
- Disponible en 30 mm, 34 mm et 35 mm

45° MONTAGE (173236)

GARANTIE À VIE LEUPOLD*

N'importe qui peut offrir une garantie à vie, mais garantir des performances demande beaucoup de sérieux et un énorme savoir-faire. De notre usine à Beaverton en Oregon, aux étendues sauvages en passant par les champs de bataille et stands de tir, nous ne vous abandonnerons pas.


Si votre lunette Leupold, jumelles, longue vue ou point rouge ne fonctionnent pas, nous les réparerons ou les remplacerons gratuitement*.

*Garantie européenne de 30ans, étendue à vie par le service commercial LEUPOLD. Composants électroniques et dommages extérieurs exclus.

Pour tous les détails, visitez leupold.com/support/lifetime-guarantee

LEUPOLD PRO GEAR

From outerwear to shooting accessories, Pro Gear is tested in the field and built to perform.
You can see the full lineup at Leupold.com.



Leupold & Stevens, Inc.
PO Box 688, Beaverton, OR 97075-0688
leupold.com 1-800-LEUPOLD (538-7653)



Retirez les piles usagées et recyclez-les immédiatement ou mettez-les au rebut conformément aux réglementations locales et tenez-les hors de portée des enfants. Ne jetez PAS les piles dans les ordures ménagères et ne les incinérez pas. Même les piles usagées peuvent provoquer des blessures graves, voire mortelles. Appelez un centre antipoison local pour obtenir des informations sur le traitement. Les piles non rechargeables ne doivent pas être rechargées. Ne pas les décharger de force, les recharger, les démonter, les chauffer au-delà de la température nominale spécifiée par le fabricant ou les incinérer. Vous risqueriez de vous blesser en raison d'un dégagement, d'une fuite ou d'une explosion entraînant des brûlures chimiques. Veillez à ce que la batterie soit installée correctement en respectant la polarité (+ et -). Ne mélangez pas des piles neuves et anciennes, des marques ou des types de piles différents, tels que les piles alcalines, les piles au carbone-zinc ou les piles rechargeables. Retirez et recyclez ou éliminez immédiatement les piles des équipements non utilisés pendant une période prolongée, conformément aux réglementations locales. Fermez toujours complètement le compartiment à piles. Si le compartiment à piles ne ferme pas correctement, arrêtez d'utiliser le produit, retirez les piles et tenez-les hors de portée des enfants.

Vous trouverez toutes les informations concernant les brevets sur www.leupold.com/legal